

	Farmall EM	Farmall Cub	Farmall A & Super A	Farmall C & Super C	Farmall H	McCormick International W-4	Farmall M	McCormick International W-6	McCormick International W-9
Cylinderdiamater	98, 43 mm.	66, 68 mm.	76, 20 mm.	76, 20 mm.	85, 72 mm.	85, 72 mm.	98, 43 mm.	98, 43 mm.	111, 76 mm.
Slaglängd	133, 35 mm.	69, 85 mm.	101, 60 mm.	101, 60 mm.	107, 95 mm.	107, 50 mm.	133, 35 mm.	133, 35 mm.	139, 70 mm.
Cylindervolym	4, 06 l.	0, 97 l.	1, 85 l.	1, 85 l.	2, 49 l.	2, 49 l.	4, 06 l.	4, 06 l.	5, 48 l.
Komp. förhållande	4, 75 : 1	5 : 1	4, 65 : 1	4, 65 : 1	4, 75 : 1	4, 75 : 1	4, 75 : 1	4, 57 : 1	4, 24 : 1
Hästkrafter vid varv/min.	36, 7	9, 8	17, 1	20, 0	24, 9	24, 9	36, 7	36, 7	49, 0
Bensintank, rymd	1450	1600	1400	1650	1650	1650	1450	1450	1500
Bränsletank, rymd	3, 5 l.	28 l.	3, 3 l.	3, 3 l.	3, 3 l.	3, 3 l.	3, 5 l.	3, 5 l.	3, 5 l.
Kylsystem, rymd	79, 5 l.	--	41, 5 l.	41, 5 l.	66, 0 l.	66, 0 l.	79, 0 l.	79, 0 l.	136, 0 l.
Motor, oljerymd	22, 7 l.	9, 2 l.	12, 3 l.	12, 3 l.	16, 0 l.	16, 0 l.	23, 0 l.	23, 0 l.	37, 0 l.
Växellåda & differential	7, 4 l.	2, 8 l.	4, 7 l.	4, 7 l.	5, 6 l.	5, 6 l.	7, 6 l.	7, 6 l.	10, 4 l.
Slutväxel, varje sida	49, 0 l.	1, 7 l.	4, 7 l.	4, 7 l.	23, 0 l.	23, 0 l.	49, 0 l.	49, 0 l.	38, 0 l.
Motorns oljetryck vid varv/min.	--	1, 0 l.	1, 4 l.	--	--	--	--	--	--
Tändningsföljd	2, 8 - 3, 2 kg/cm ² .	2, 1 - 2, 3 kg/cm ² .	3, 8 - 4, 2 kg/cm ² .	3, 8 - 4, 2 kg/cm ² .	3, 8 - 4, 2 kg/cm ² .	3, 8 - 4, 2 kg/cm ² .	4, 2 - 4, 9 kg/cm ² .	4, 2 - 4, 9 kg/cm ² .	4, 2 - 4, 9 kg/cm ² .
Tändstiftsgap	1450	1600	1400	1650	1650	1650	1450	1450	1500
Avbrytarspetsar, avstånd	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2	1-3-4-2
Magnet & rotation batt. tänd.	0, 58 mm.	0, 58 mm.	0, 58 mm.	0, 58-0, 69 mm.	0, 58 mm.	0, 58 mm.	0, 58 mm.	0, 58 mm.	0, 70-0, 80 mm.
Ventilavst. : Insug	0, 35 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.	0, 33 mm.
Varm motor: Avgas	A-4 el.	J-4	H-4	H-4	H-4	H-4	H-4	H-4	H-4
Insug öppnar	batt. tänd.	Medsols	Medsols	Medsols	Medsols	Medsols	Medsols	Medsols	Medsols
Momentdragn. av topplocksbultar	0, 43 mm.	0, 33 mm.	0, 36 mm.	0, 36 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.
Förgasartyp	0, 43 mm.	0, 33 mm.	0, 36 mm.	0, 36 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.	0, 43 mm.
Luftkåna	10° f. Ö. D.	--	15° eftr. Ö. D.	--	5° eftr. Ö. D.	5° eftr. Ö. D.	5° eftr. Ö. D.	5° eftr. Ö. D.	5° eftr. Ö. D.
Reglernflar	15 - 16 kgm.	6, 2 - 6, 9 kgm.	9, 0-10, 0 kgm.	9, 0 - 10, 0 kgm.	9, 0 - 10, 0 kgm.	9, 0 - 10, 0 kgm.	15 - 16 kgm.	15 - 16 kgm.	22 kgm.
Flottörhöjd	Zenith	IH	Zenith, Marvel, Schebler eller Carter	IH	IH	IH	IH	IH	IH
Däckdim. fram	Nr 27	3/4"	7/8"	7/8"	1"	1"	1 1/4"	1 1/4"	1 3/8"
bak	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle	Luft & Bränsle
Ringtryck fram	43 mm.	14, 3 - 15, 9 mm.	29, 4 mm.	29, 4 mm.	46, 8 mm.	46, 8 mm.	33, 3 mm.	33, 3 mm.	33, 3 mm.
bak	6, 00-16	4, 00 - 12	4, 00 - 15	4, 00 - 15	5, 50-16	5, 50-16	6, 00-16	6, 00 - 16	7, 50-18
Toe/in	11, 00-38	8, 00 - 24	9, 00 - 24	9, 00 - 36	10, 00-38	13, 00-26	11, 00-38	14, 00-30	14, 00-34
	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .	2, 0 kg/cm ² .
	0, 8-1, 7 kg/cm ²	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .	1, 25 kg/cm ² .
	5-8 mm.	3-6 mm.	3-6 mm.	3-6 mm.	6-9 mm.	6-9 mm.	3-6 mm.	3-6 mm.	9, 5 mm.